

## **Spec Sheet**

# SMD Power Inductors (NR series)

## NR6020T4R7N





#### Features

- Item Summary 4.7uH±30%, 2A, 6.0x6.0x2.0mm
- Lifecycle Stage

Mass Production

Standard packaging quantity (minimum)
 Taping Embossed 2500pcs


#### ■ Products characteristics table

Inductance	4.7 uH ± 30 %
Case Size (mm)	6.0x6.0
Rated Current (max)	2 A
Saturation Current (max)	2.4 A
Temperature Rise Current (max)	2 A
DC Resistance (max)	69.6 mΩ
DC Resistance (typ)	58 mΩ
LQ Measuring Frequency	100 kHz
Self Resonant Frequency (min)	43 MHz
Operating Temp. Range	-25 to +120 ℃ (Including-self-generated heat)
Temperature characteristic (Inductance change)	± 20 %
RoHS2 Compliance (10 subst.)	Yes
REACH Compliance (173 subst.)	Yes
Halogen Free	Yes
Soldering	Reflow

#### External Dimensions

Dimension L	6.0 ±0.2 mm
Dimension W	6.0 ±0.2 mm
Dimension H	Max 2.0 mm
Dimension e	1.35 ±0.2 mm
Dimension f	4.0 ±0.2 mm
Dimension ΔI	Typ 2.3 mm

## Recommended Land Patterns



2017.04.30

## SMD Power Inductors (NR series)

### NR6020T4R7N



Dimension unit: mm unit: inch

Length: 6.0 + / - 0.2 (0.236 + / - 0.008)

Width: 6.0 + / - 0.2 (0.236 + / - 0.008)

Height: 2.0 max. (0.079 max.)

Inductance: 4.7 uH (test freq at 0.1MHz)
DC Resistance: 0.058 / 0.0696 ohm (typ/max)

Saturation Current: 2,400 mA (max) Temp. rise Current: 2,000 mA (max)

Saturation current typical: 30% reduction from initial L value.

Temp rise Current typical: Temperature will rise by 40 deg C

